



MODELLO MAPS40 MODEL MAPS40

CODICE
CODE



MAPS40G1/8

0/6

B/P

1

2

3

1	CONNESSIONE AL PROCESSO PROCESS CONNECTION	CODICE CODE	2	SCALA RANGE	CODICE CODE	SCALA RANGE	CODICE CODE
	1/8" gas cilindrico	G1/8		-1 ... 0	-1/0	0 ... 10	0/10
	1/8"npt	N1/8		-1 ... 0.6	-1/0.6	0 ... 12	0/12
	1/8" gas conico	R1/8		-1 ... 1.5	-1/1.5	0 ... 16	0/16
	Altro/another	*		-1 ... 3	-1/3	0 ... 20	0/20
				-1 ... 5	-1/5	0 ... 25	0/25
				-1 ... 9	-1/9	0 ... 40	0/40
				-1 ... 15	-1/15	0 ... 60	0/60
				-1 ... 24	0/24	0 ... 100	0/100
				0 ... 0.6	0/0.6	0 ... 160	0/160
				0 ... 1	0/1	0 ... 200	0/200
				0 ... 1.6	0/1.6	0 ... 250	0/250
				0 ... 2.5	0/2.5	0 ... 315	0/315
				0 ... 4	0/4	0 ... 400	0/400
				0 ... 6	0/6	0 ... 600	0/600
				Altro/another	*		*

3	UNITÀ DI MISURA UNIT	CODICE CODE
	bar	B
	bar / psi	B/P
	psi	P
	Kpa	K
	Mpa	M
	Altro/another	*



- | | |
|--|--|
| <ul style="list-style-type: none"> manometro molla bourdon | <ul style="list-style-type: none"> bourdon tube pressure gauge |
| <ul style="list-style-type: none"> materiale cassa in Acciaio Nero diametro cassa 40 mm con staffa posteriore | <ul style="list-style-type: none"> Black Steel nominal size 40 mm with u-clamp back |
| <ul style="list-style-type: none"> esecuzione posteriore | <ul style="list-style-type: none"> center back |
| <ul style="list-style-type: none"> attacco al processo lega di rame | <ul style="list-style-type: none"> process connection copper alloy |
| <ul style="list-style-type: none"> elemento di misura lega di rame | <ul style="list-style-type: none"> pressure element copper alloy |
| <ul style="list-style-type: none"> movimento lega di rame | <ul style="list-style-type: none"> movement copper alloy |
| <ul style="list-style-type: none"> classe di precisione 2,5% f.s. | <ul style="list-style-type: none"> accuracy class 2,5% |
| <ul style="list-style-type: none"> quadrante alluminio bianco con fermo a zero | <ul style="list-style-type: none"> dial aluminium white with pointer stop pin |
| <ul style="list-style-type: none"> indice alluminio | <ul style="list-style-type: none"> index aluminium |
| <ul style="list-style-type: none"> trasparente in plastica | <ul style="list-style-type: none"> window plastic |
| <ul style="list-style-type: none"> normativa EN 837-1 | <ul style="list-style-type: none"> design EN 837-1 |
| <ul style="list-style-type: none"> temperatura ambiente -20 ... +60°C fluido +60°C | <ul style="list-style-type: none"> temperature ambient -20 ... +60°C fluid +60°C |