



MODELLO MTIPGFA50 MODEL MTIPGFA50

CODICE
CODE



MTIPGFA50G1/4

0/6

B/P

1

2

3

1	CONNESSIONE AL PROCESSO PROCESS CONNECTION	CODICE CODE	2	SCALA RANGE	CODICE CODE	SCALA RANGE	CODICE CODE
	1/4" gas cilindrico	G1/4		-1 ... 0	-1/0	0 ... 10	0/10
	1/4"npt	N1/4		-1 ... 0.6	-1/0.6	0 ... 12	0/12
	1/4" gas conico	R1/4		-1 ... 1.5	-1/1.5	0 ... 16	0/16
	1/8" gas cilindrico	G1/8		-1 ... 3	-1/3	0 ... 20	0/20
	1/8"npt	N1/8		-1 ... 5	-1/5	0 ... 25	0/25
	1/8" gas conico	R1/8		-1 ... 9	-1/9	0 ... 40	0/40
	Altro/another	*		-1 ... 15	-1/15	0 ... 60	0/60
				-1 ... 24	0/24	0 ... 100	0/100
				0 ... 0.6	0/0.6	0 ... 160	0/160
				0 ... 1	0/1	0 ... 200	0/200
				0 ... 1.6	0/1.6	0 ... 250	0/250
				0 ... 2.5	0/2.5	0 ... 315	0/315
				0 ... 4	0/4	0 ... 400	0/400
				0 ... 6	0/6	0 ... 600	0/600
				Altro/another			*
3	UNITÀ DI MISURA UNIT	CODICE CODE					
	bar	B					
	bar / psi	B/P					
	psi	P					
	Kpa	K					
	Mpa	M					
	Altro/another	*					



• manometro molla bourdon

- materiale cassa in Acciaio Inox diametro cassa 50 mm con flangia anteriore a 3 fori e riempimento di glicerina

• esecuzione posteriore

- attacco al processo Acciaio Inox

• elemento di misura Acciaio Inox

- movimento Acciaio Inox

• classe di precisione 1,6% f.s.

- quadrante alluminio bianco con fermo a zero

• indice alluminio

- trasparente in policarbonato

• normativa EN 837-1

- temperatura ambiente -20 ... +60°C fluido +100°C

• bourdon tube pressure gauge

- case Stainless Steel nominal size 50 mm with front flange 3 hole and with glycerine

• center back

- process connection stainless steel

• pressure element stainless steel

- movement Stainless Steel

• accuracy class 1,6%

- dial aluminium white with pointer stop pin

• index aluminium

- window polycarbonate

• design EN 837-1

- temperature ambient -20 ... +60°C fluid +100°C