




# MODELLO MTIRSM100 MODEL MTIRSM100

## CODICE CODE



1	CONNESSIONE AL PROCESSO PROCESS CONNECTION	CODICE CODE	2	SCALA RANGE	CODICE CODE	SCALA RANGE	CODICE CODE
	1/2" gas cilindrico	G1/2		-1 ... 0	-1/0	0 ... 6	0/6
	1/2"npt	N1/2		-1 ... 0.6	-1/0.6	0 ... 10	0/10
	1/2" gas conico	R1/2		-1 ... 1.5	-1/1.5	0 ... 12	0/12
	Altro/another	*		-1 ... 3	-1/3	0 ... 16	0/16
				-1 ... 5	-1/5	0 ... 25	0/25
				-1 ... 9	-1/9	0 ... 40	0/40
				-1 ... 15	-1/15	0 ... 60	0/60
				-1 ... 24	0/24	0 ... 100	0/100
				0 ... 0.6	0/0.6	0 ... 160	0/160
				0 ... 1	0/1	0 ... 200	0/200
				0 ... 1.6	0/1.6	0 ... 250	0/250
				0 ... 2.5	0/2.5	0 ... 400	0/400
				0 ... 4	0/4	0 ... 600	0/600
				Altro/another	*		



- manometro a membrana
- materiale cassa in Acciaio Inox diametro cassa 100 mm
- esecuzione radiale
- attacco al processo Acciaio Inox
- elemento di misura Acciaio Inox
- movimento Acciaio Inox
- classe di precisione 1% f.s.
- quadrante alluminio bianco con fermo a zero
- indice alluminio
- trasparente vetro multistrato di sicurezza
- temperatura ambiente -20 ... +60°C fluido + 100°C



- membrane pressure gauge
- case Stainless Steel nominal size 100 mm
- lower mount
- process connection stainless steel
- pressure element stainless steel
- movement stainless steel
- accuracy class 1%
- dial aluminium white with pointer stop pin
- index aluminium
- window safety glass
- temperature ambient -20 ... +60°C fluid + 100°C