



- thermo manometer
- plastic black nominal size 80 mm
- center back
- process connection copper alloy
- pressure element copper alloy
- movement copper alloy accuracy class 2,5% f.s.
- dial aluminium white with pointer stop pin
- index aluminium
- window plastic
- thermometer element copper alloy

Model MPPTP80

process connection

Range	Unit	3/8" cylindrical gas	3/8" npt	3/8" conical gas
0 ... 2.5 / 0 ... 100 °C	bar / °C	MPPTP80G3/8-0/2.5-B-0/100-C	MPPTP80N3/8-0/2.5-B-0/100-C	MPPTP80R3/8-0/2.5-B-0/100-C
0 ... 2.5 / 0 ... 120 °C	bar / °C	MPPTP80G3/8-0/2.5-B-0/120-C	MPPTP80N3/8-0/2.5-B-0/120-C	MPPTP80R3/8-0/2.5-B-0/120-C
0 ... 2.5 / 0 ... 140 °C	bar / °C	MPPTP80G3/8-0/2.5-B-0/140-C	MPPTP80N3/8-0/2.5-B-0/140-C	MPPTP80R3/8-0/2.5-B-0/140-C
0 ... 2.5 / 0 ... 160 °C	bar / °C	MPPTP80G3/8-0/2.5-B-0/160-C	MPPTP80N3/8-0/2.5-B-0/160-C	MPPTP80R3/8-0/2.5-B-0/160-C
0 ... 2.5 / 0 ... 200 °C	bar / °C	MPPTP80G3/8-0/2.5-B-0/200-C	MPPTP80N3/8-0/2.5-B-0/200-C	MPPTP80R3/8-0/2.5-B-0/200-C
0 ... 4 / 0 ... 100 °C	bar / °C	MPPTP80G3/8-0/4-B-0/100-C	MPPTP80N3/8-0/4-B-0/100-C	MPPTP80R3/8-0/4-B-0/100-C
0 ... 4 / 0 ... 120 °C	bar / °C	MPPTP80G3/8-0/4-B-0/120-C	MPPTP80N3/8-0/4-B-0/120-C	MPPTP80R3/8-0/4-B-0/120-C
0 ... 4 / 0 ... 140 °C	bar / °C	MPPTP80G3/8-0/4-B-0/140-C	MPPTP80N3/8-0/4-B-0/140-C	MPPTP80R3/8-0/4-B-0/140-C
0 ... 4 / 0 ... 160 °C	bar / °C	MPPTP80G3/8-0/4-B-0/160-C	MPPTP80N3/8-0/4-B-0/160-C	MPPTP80R3/8-0/4-B-0/160-C
0 ... 4 / 0 ... 200 °C	bar / °C	MPPTP80G3/8-0/4-B-0/200-C	MPPTP80N3/8-0/4-B-0/200-C	MPPTP80R3/8-0/4-B-0/200-C
0 ... 6 / 0 ... 100 °C	bar / °C	MPPTP80G3/8-0/6-B-0/100-C	MPPTP80N3/8-0/6-B-0/100-C	MPPTP80R3/8-0/6-B-0/100-C
0 ... 6 / 0 ... 120 °C	bar / °C	MPPTP80G3/8-0/6-B-0/120-C	MPPTP80N3/8-0/6-B-0/120-C	MPPTP80R3/8-0/6-B-0/120-C
0 ... 6 / 0 ... 140 °C	bar / °C	MPPTP80G3/8-0/6-B-0/140-C	MPPTP80N3/8-0/6-B-0/140-C	MPPTP80R3/8-0/6-B-0/140-C
0 ... 6 / 0 ... 160 °C	bar / °C	MPPTP80G3/8-0/6-B-0/160-C	MPPTP80N3/8-0/6-B-0/160-C	MPPTP80R3/8-0/6-B-0/160-C
0 ... 6 / 0 ... 200 °C	bar / °C	MPPTP80G3/8-0/6-B-0/200-C	MPPTP80N3/8-0/6-B-0/200-C	MPPTP80R3/8-0/6-B-0/200-C
0 ... 10 / 0 ... 100 °C	bar / °C	MPPTP80G3/8-0/10-B-0/100-C	MPPTP80N3/8-0/10-B-0/100-C	MPPTP80R3/8-0/10-B-0/100-C
0 ... 10 / 0 ... 120 °C	bar / °C	MPPTP80G3/8-0/10-B-0/120-C	MPPTP80N3/8-0/10-B-0/120-C	MPPTP80R3/8-0/10-B-0/120-C
0 ... 10 / 0 ... 140 °C	bar / °C	MPPTP80G3/8-0/10-B-0/140-C	MPPTP80N3/8-0/10-B-0/140-C	MPPTP80R3/8-0/10-B-0/140-C
0 ... 10 / 0 ... 160 °C	bar / °C	MPPTP80G3/8-0/10-B-0/160-C	MPPTP80N3/8-0/10-B-0/160-C	MPPTP80R3/8-0/10-B-0/160-C
0 ... 10 / 0 ... 200 °C	bar / °C	MPPTP80G3/8-0/10-B-0/200-C	MPPTP80N3/8-0/10-B-0/200-C	MPPTP80R3/8-0/10-B-0/200-C
0 ... 16 / 0 ... 100 °C	bar / °C	MPPTP80G3/8-0/16-B-0/100-C	MPPTP80N3/8-0/16-B-0/100-C	MPPTP80R3/8-0/16-B-0/100-C
0 ... 16 / 0 ... 120 °C	bar / °C	MPPTP80G3/8-0/16-B-0/120-C	MPPTP80N3/8-0/16-B-0/120-C	MPPTP80R3/8-0/16-B-0/120-C
0 ... 16 / 0 ... 140 °C	bar / °C	MPPTP80G3/8-0/16-B-0/140-C	MPPTP80N3/8-0/16-B-0/140-C	MPPTP80R3/8-0/16-B-0/140-C
0 ... 16 / 0 ... 160 °C	bar / °C	MPPTP80G3/8-0/16-B-0/160-C	MPPTP80N3/8-0/16-B-0/160-C	MPPTP80R3/8-0/16-B-0/160-C
0 ... 16 / 0 ... 200 °C	bar / °C	MPPTP80G3/8-0/16-B-0/200-C	MPPTP80N3/8-0/16-B-0/200-C	MPPTP80R3/8-0/16-B-0/200-C