



- isometric pressure gauge
- case Stainless Steel nominal size 100 mm with glycerine
- lower mount
- process connection copper alloy
- movement copper alloy
- accuracy class 1,6%
- dial aluminium white with pointer stop pin
- index aluminium
- window polycarbonate
- operation temperature -10...+65°C
- operating pressure 75%

Model MIXRG100		process connection	
Range	Unità	1/2" gas	1/2" npt
0 ... 5 Green 5 ... 20 Yellow 20 ... 25 Red	bar	MIXRG100G1/2-0/25-B-5G-20Y-25R	MIXRG100N1/2-0/25-B-5G-20Y-25R
0 ... 8 Green 8 ... 20 Yellow 20 ... 25 Red	bar	MIXRG100G1/2-0/25-B-8G-20Y-25R	MIXRG100N1/2-0/25-B-8G-20Y-25R
0 ... 15 Green 15 ... 25 Yellow 25 ... 60 Red	bar	MIXRG100G1/2-0/60-B-15G-25Y-60R	MIXRG100N1/2-0/60-B-15G-25Y-60R
0 ... 20 Green 20 ... 40 Yellow 40 ... 60 Red	bar	MIXRG100G1/2-0/60-B-20G-40Y-60R	MIXRG100N1/2-0/60-B-20G-40Y-60R