



- membrane pressure gauge
- case Stainless Steel nominal size 100 mm
- lower mount
- process connection Stainless Steel
- pressure element Stainless Steel
- movement Stainless Steel
- accuracy class 1%
- dial aluminium white with pointer stop pin
- index aluminium
- window safety glass
- temperature ambient -20 ... +60°C fluid +100°C

Model MTIRSM100

process connection

Range	Unit	1/2" cylindrical gas	1/2" npt
0 ...1	bar	MTIRSM100G1/2-0/1-B	MTIRSM100N1/2-0/1-B
0 ...1.6	bar	MTIRSM100G1/2-0/1.6-B	MTIRSM100N1/2-0/1.6-B
0 ...2.5	bar	MTIRSM100G1/2-0/2.5-B	MTIRSM100N1/2-0/2.5-B
0 ...4	bar	MTIRSM100G1/2-0/4-B	MTIRSM100N1/2-0/4-B
0 ...6	bar	MTIRSM100G1/2-0/6-B	MTIRSM100N1/2-0/6-B
0 ...10	bar	MTIRSM100G1/2-0/10-B	MTIRSM100N1/2-0/10-B
0 ...16	bar	MTIRSM100G1/2-0/16-B	MTIRSM100N1/2-0/16-B
0 ...25	bar	MTIRSM100G1/2-0/25-B	MTIRSM100N1/2-0/25-B
0 ...40	bar	MTIRSM100G1/2-0/40-B	MTIRSM100N1/2-0/40-B