



- membrane pressure gauge
- case S tainless Steel nominal size 160 mm
- lower mount
- process connection S tainless Steel
- pressure element S tainless Steel
- movement S tainless Steel
- accuracy class 1%
- dial aluminium white with pointer stop pin
- index aluminium
- window safety glass
- tem perature ambient -20 ... +60 °C fluid +100 °C

Model MTIRSM160
process connection

Range	Unit	process connection	
		1/2" cylindrical gas	1/2" npt
0 ...1	bar	MTIRSM160G1/2-0/1-B	MTIRSM160N1/2-0/1-B
0 ...1.6	bar	MTIRSM160G1/2-0/1.6-B	MTIRSM160N1/2-0/1.6-B
0 ...2.5	bar	MTIRSM160G1/2-0/2.5-B	MTIRSM160N1/2-0/2.5-B
0 ...4	bar	MTIRSM160G1/2-0/4-B	MTIRSM160N1/2-0/4-B
0 ...6	bar	MTIRSM160G1/2-0/6-B	MTIRSM160N1/2-0/6-B
0 ...10	bar	MTIRSM160G1/2-0/10-B	MTIRSM160N1/2-0/10-B
0 ...16	bar	MTIRSM160G1/2-0/16-B	MTIRSM160N1/2-0/16-B
0 ...25	bar	MTIRSM160G1/2-0/25-B	MTIRSM160N1/2-0/25-B
0 ...40	bar	MTIRSM160G1/2-0/40-B	MTIRSM160N1/2-0/40-B