



- isometric pressure gauge
- case Stainless Steel nominal size 100 mm with glycerine
- lower mount
- process connection Stainless Steel
- movement Stainless Steel
- accuracy class 1,6%
- dial aluminium white with pointer stop pin
- index aluminium
- window polycarbonate
- operation temperature -10...+65 °C
- operating pressure 75%

## Model MITXRG100

## process connection

| Range                                               | Unit | 1/2" gas                         | 1/2" npt                          |
|-----------------------------------------------------|------|----------------------------------|-----------------------------------|
| 0 ... 5 Green<br>5 ... 20 Yellow<br>20 ... 25 Red   | bar  | MTIXRG100G1/2-0/25-B-5G-20Y-25R  | MTIXRG100N1/2-0/25-B-5G-20Y-25R   |
| 0 ... 8 Green<br>8 ... 20 Yellow<br>20 ... 25 Red   | bar  | MTIXRG100G1/2-0/25-B-8G-20Y-25R  | MTIXRG100N1/2-0/25-B-8G-20Y-25R   |
| 0 ... 15 Green<br>15 ... 25 Yellow<br>25 ... 60 Red | bar  | MTIXRG100G1/2-0/60-B-15G-25Y-60R | MTIXRG100N1/2-0/60-B-15G-25Y-60R  |
| 0 ... 20 Green<br>20 ... 40 Yellow<br>40 ... 60 Red | bar  | MTIXRG100G1/2-0/60-B-20G-40Y-60R | MTIXRG100N1/2-0/60-B-20G-40Y-60RT |