



MODELLO MTIXRG63 MODEL MTIXRG63

CODICE
CODE

MTIXRG63G1/4

0/25-B-5G-20Y-25R

1

2



1	CONNESSIONE AL PROCESSO PROCESS CONNECTION	CODICE CODE	2	SCALA RANGE	CODICE CODE
	1/4" gas cilindrico	G1/4		0...5 Verde/Green	
	1/4"npt	N1/4		5 ... 20 Giallo/Yellow	0/25-B-5G-20Y-25R
	1/4" gas conico	R1/4		20 ... 25 Rosso/Red	
	Altro/another	*		0...8 Verde/Green	
				8 ... 20 Giallo/Yellow	0/25-B-8G-20Y-25R
				20 ... 25 Rosso/Red	
				0...15 Verde/Green	
				15 ... 25 Giallo/Yellow	0/60-B-15G-25Y-60R
				25 ... 60 Rosso/Red	
				0...20 Verde/Green	
				20 ... 40 Giallo/Yellow	0/60-B-20G-40Y-60R
				40 ... 60 Rosso/Red	



• manometro isometrico	• isometric pressure gauge
• diametro cassa 63 mm con riempimento di glicerina	• case Stainless Steel nominal size 63 mm with glycerine
• esecuzione posteriore	• center back
• trasparente in policarbonato	• window polycarbonate
• movimento in Acciaio Inox	• movement Stainless Steel
• attacco al processo in Acciaio Inox	• process connection Stainless Steel
• quadrante in alluminio	• dial aluminium white with pointer stop pin
• lancetta in alluminio	• index aluminium
• classe di precisione 1.6% f.s.	• accuracy class 1,6%
• temperatura di esercizio -10 ... +65°C	• operatin temperature -10 ... +65°C
• pressione di esercizio 75%	• operating pressure 75%