



## MODELLO MTIR100SPVC MODEL MTIR100SPVC



### CODICE

CODE

MTIR100SPVCG1/2

1

0/10

2

B

3

### 1 CONNESSIONE AL PROCESSO

PROCESS CONNECTION

	Codice/Code
1/2" gas cilindrico	G1/2
1/2" gas conico	R1/2
1/2" NPT	N1/2
Altro/Another	*

### 3 UNITÀ DI MISURA

UNIT

	Codice/Code
Bar	B
Bar/Psi	B/P
Psi	P
Kpa	K
Mpa	M
Kg/cm <sup>2</sup>	KG/CM <sup>2</sup>
Altro / Another	*

### 2 SCALA

RANGE

Codice  
Code

### SCALA

RANGE

Codice  
Code

-1... 0	-1/0	0... 12	0/12
-1... 0.6	-1/0.6	0... 16	0/16
-1... 1.5	-1/1.5	0... 20	0/20
-1... 3	-1/3	0... 25	0/25
-1... 5	-1/5	0... 40	0/40
-1... 9	-1/9	0... 60	0/60
-1... 15	-1/15	0... 100	0/100
-1... 24	-1/24	0... 160	0/160
0... 0.6	0/0.6	0... 200	0/200
0... 1	0/1	0... 250	0/250
0... 1.6	0/1.6	0... 315	0/315
0... 2.5	0/2.5	0... 400	0/400
0... 4	0/4	0... 600	0/600
0... 6	0/6	0... 1000	0/1000
0... 10	0/10	Altro / Another	

Manometro a molla bourdon con separatore a membrana in PVC

Diametro cassa: 100 mm

Esecuzione: Radiale

Normativa: EN 837-1

Classe di precisione: 1%

Attacco al processo: Acciaio Inox 316L

Elemento di misura: Acciaio Inox 316L

Movimento: Acciaio Inox 316L

Quadrante: In alluminio a fondo bianco, numerazione in nero con fermo sullo zero

Indice: in alluminio di colore nero

Trasparente: Vetro multistrato di sicurezza

Materiale della cassa e anello: Acciaio Inox

Foro di scarico posteriore

Bourdon tube pressure gauge with diaphragm

Nominal Size: 100 mm

Bottom

Design: EN 837-1

Accuracy Class: 1%

Process connection: Stainless Steel 316L

Pressure element: Stainless Steel 316L

Moviment: Stainless Steel 316L

Dial: White aluminium with black marks

Black anodized aluminium


Window: Safety Glass

Case and Ring: Stainless Steel

With blow-out device at case circumference and on the back of the case



## MODELLO MTIR100SPVC MODEL MTIR100SPVC



+/- 0.1	A	B	C	D	E	F	G	H
DN40	46.9	41	22	9.55	10.9	4.7	25.6	12
DN50	57.6	50.9	29	12.95	13.95	6.3	29.6	16
DN63	68	61.8	29	12.95	13.95	6.3	29.6	16
DN100	100.8	98.5	41	20.8	22	17	48.7	20
DN160	160	158	44	20.8	22	17	49.8	20

CONDIZIONI DI ESERCIZIO	OPERATING CONDITIONS
Temperatura ambiente: -30 ... +60°C	Ambient Temperature: -30 ... +60°C
Temperatura fluido di processo: -30 ... +120°C	Process fluid temperature: -30 ... +120°C
Deriva termica: massimo $\pm 0.3\%$ dell'ampiezza di campo ogni 10°C di differenza dalla temperatura di riferimento di 20°C	Thermal drift: maximum $\pm 0.3\%$ of span every 10°C of deviation from the reference temperature of 20°C
Pressione d'esercizio costante: 75% del fondo scala	Operating pressure constant: 75% del F.S.V.
Pressione d'esercizio variabile: 60% del fondo scala	Operating pressure changeable: 60% F.S.V.
Sovrapressione fino a 60 bar: 25% del fondo scala	Overpressure up to 60 bar: 25% F.S.V.
Sovrapressione > 100 bar: 15% del fondo scala	Overpressure from > 100 bar: 15% F.S.V.
Grado di protezione IP65 conforme EN 60529 / IEC 60529	Protection EN 60529 / IEC 60529 IP65

### OPZIONI

- Materiale Cassa e Anello in AISI 316L
- Flangia a 3 fori in Acciaio Inox

### OPTION

- Case and Ring material AISI 316 L
- Front Flange 3 hole Stainless Steel

## CERTIFICAZIONI

### CERTIFICATE

- **Certificato di taratura conforme a ISO/IEC 17025 3.1b**  
Calibration report ISO / IEC 17025 3.1b
- **Certificato taratura organismo accreditato nazionale**  
National Accredited Calibration Certificate
- **Certificato origine camera commercio**  
Certificate of origin Chamber of Commerce
- **Certificazione di prova 2.2 conforme EN 10204 (produzione stato dell'arte, precisione indicazione)**  
Certificate 2.2 EN 10204
- **Certificazione 3.1 conforme ad EN 10204 (cert. Materiale)**  
Certificate 3.1 EN 10204 (material certificate)



# Diaphragm pressure gauge guard

## MTIR100SPVC

Nominal size DN 20–25  
Pressure PN 10 bar



### Features

- Pressure measurement up to 10 bar
- EPDM diaphragm with PTFE coating on the side in contact with the medium
- Reliable protection of pressure gauges from aggressive medium types
- Reliable pressure transmission due to generously dimensioned diaphragms
- Practical connection points with spigots and threads

### Additional options on demand

- Free of surface disturbing substances
- NSF certification
- PFA permeation stop films
- Installation of different pressure gauges

### Attention


Diaphragm pressure gauge guard free of surface disturbing substances is filled with demineralized water

**CONTROL PROCESS srl**  
Via Anzalone, 22  
95024-Acireale  
**Telefono** +39 095 721 38 41  
**Fax** + 39 095 721 07 12

**email:** [info@controlprocess.it](mailto:info@controlprocess.it)



# Pictogram Diaphragm pressure gauge guard MTIR100SPVC



**Diffusion stop** for medium types prone to permeation:  
PFA permeation stop film  
Available versions: PVC-U | PVDF

● available  
○ not available

## Basic Nominal Sizes:

DN 8	DN 10	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 125	DN 150	DN 200	DN 250	DN 300	DN 350	DN 400
------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--------	--------	--------	--------	--------	--------	--------	--------

## Connection Material (process connection)

spigot **DIN\*** + female thread **G**  
female thread (reinforced) **NPT**  
female thread **G**

\*socket welding

**CONTROL PROCESS srl**  
Via Anzalone, 22 - 95024 Acireale  
**Telefono** +39 095 721 38 41 - **Fax** + 39 095 721 07 12

**email:** [info@controlprocess.it](mailto:info@controlprocess.it)



# Diaphragm pressure gauge guard MTIR100SPVC

## Use

- Chemical plant engineering
- Electroplating plants

## Application

- for corrosion-free pressure transmission between the medium and the measuring instrument

## Pressure transmission

- The system pressure is transmitted to the measuring instrument by a large diaphragm via transmitter fluid

## Flow medium

- Neutral and aggressive fluids free of solid particles, provided that the valve components coming into contact with the fluids are resistant at the operating temperature according to the ASV resistance guide

## ASV-Stübbe resistance guide

- [www.asv-stuebbe.de/pdf\\_resistance/300051.pdf](http://www.asv-stuebbe.de/pdf_resistance/300051.pdf)

## Nominal pressure (H<sub>2</sub>O, 20 °C)

- PN 10 bar

## Medium temperature

- See graphics „Pressure/temperature diagram“

## Operating pressure

- See graphics „Pressure/temperature diagram“

## Size

- DN 20–25

## Bonnet

- PP, glass fiber reinforced

## Bottom section

- PVC-U, PP, PVDF

## Sealing element

- PTFE, PFA

## Diaphragm

- PTFE (EPDM diaphragm with PTFE coating on the side in contact with the medium)
- Optional: PFA permeation stop film

## Transmitter fluid

- Glycol (ethylene glycol)
- Antifreeze (e.g. glysantine or Aral Antifreeze)
- Demineralized water: When used for potable water or for free of surface disturbing substances

## Device connection

- See pictogram

## Pressure gauge connection

- Bonnet, internal thread G 1/4", G 1/2", NPT 1/4", NPT 1/2"
- Rear connection G1/4" – only for standard pressure gauge design

## Mounting position

- As required, preferably measuring instrument at the top

## Color

### Bonnet:

- orange, RAL 2004

### Bottom section:

- PVC-U: gray, RAL 7011
- PP: gray, RAL 7032
- PVDF: opaque, yellowish-white

## Accessories

### Pressure gauge, standard version:

- Housing: POM
- Measuring system: Copper alloy

### Pressure gauge chemical version (undamped, damped):

- Housing: CrNi steel (1,4571)
- Measuring system: CrNi steel (1,4571)

### Pressure transducer

## CONTROL PROCESS srl

Via Anzalone, 22 - 95024 Acireale



Telefono +39 095 721 38 41 - Fax + 39 095 721 07 12

email: [info@controlprocess.it](mailto:info@controlprocess.it)



# Diaphragm pressure gauge guard MTIR100SPVC


## Pressure/temperature diagram



The pressure/temperature limits of the materials are valid for the stated nominal pressures and a service life of 25 years.


These values are guide values for flow medium types which do not negatively impact the physical and chemical characteristics of the valve material. It may be necessary to take diminution factors into consideration.

The operating life of the wear parts depends on the conditions of use.



### Description

P	Operating pressure
T	Temperature



### Connection spigot end

	25	32
d (mm)	25	32
DN (mm)	20	25
G (inch)	1/4	1/2
D	80.0	80.0
d	25.0	32.0
G*	1/4	1/2
h	86.0	86.0
t	18.0	22.0

all dimensions in mm / \* dimensions in inch

**CONTROL PROCESS srl**


Via Anzalone, 22 - 95024 Acireale

Telefono +39 095 721 38 41 - Fax + 39 095 721 07 12

email: [info@controlprocess.it](mailto:info@controlprocess.it)


# Diaphragm pressure gauge guard MTIR100SPVC

## Structure



Position	Designation
1	Connection, pressure gauge
2	Bonnet
3	Separating diaphragm
4	Bottom section

## Components



Position	Designation
1	Pressure gauge
2	Bonnet
3	Flat sealing
4	Transmitter fluid
5	Separating diaphragm
6	Bottom section